

□□ □□□□ □□
□□□□ □□□□□ & □□□□



icetek ၵᄃᄃ ၵᄃᄃᄃᄃ ၵᄃᄃᄃ ᄃ ᄃᄃᄃ, ᄃ ᄃᄃᄃ ᄃ 3mm ᄃᄃᄃ, ᄃᄃᄃ, ᄃᄃᄃ ᄃ ᄃ ᄃ 2mm ᄃᄃᄃᄃ V2 3 ᄃ 360 ᄃᄃ ᄃᄃᄃ, ᄃᄃ ᄃᄃ ᄃᄃᄃ ᄃᄃ ᄃᄃ ᄃ ᄃᄃᄃ.

□□□□ □□:

- 1 0000 000000 (約 2 kg)
- 1 000 0000 Ø 9.5 mm (3/8"UNF) – Ø 19 mm (3/4"UNF), L: 105 mm
- 1 000 0000 Ø 19.5 mm (3/4"UNF), L: 125 mm
- 1 0000 0
- 1 0000
- 1 HSS 0000 (Multi Step Drill)
- 1 000000 000000
- 000000 00 PRO 16-32: M16, M20, M25, M32 000 00 0 10
- 000000 00 PRO 16-63: M16, M20, M25, M32, M40, M50, M63 000 00 0 10
- 000000 00 PRO 16-63 V2A: M16, M20, M25, M32, M40, M50, M63 (000000 0000) 000 00 0 10

□□□ □ □□

이 제품은 450bar의 압력을 견딜 수 있습니다. 이 압력은, 모든 종류의 차량을 가압할 수 있습니다. 이 제품은 100% 알루미늄으로 제작되었습니다.

□□□□ □□:

- 1 吋 砲
- 砲 砲砲 砲 2.5m 砲 砲砲 砲
- 1 砲 砲 砲砲 砲 砲砲砲
- 1 砲 砲砲(砲) 砲 砲砲 M16-M25
- 1 砲 砲砲(砲) 砲 砲砲 M32-M85
- 1 砲砲 砲
- 1 砲砲
- 1 砲 砲砲

00. 00000 000

□□ □□ □□ □□

- 360도 회전 가능, 2kg까지 무게를 올려도 OK
- 100% 재활용 소재로 제작
- 100% 무독성, 무취
- 100% 무균, 무균
- 100% 무균, 무균

□□ □□ □ □□



EAN

80002
4251269323690
1
60 kN
450 bar



EAN 80003
4251269332
432
1
007400 00 0000, 00(St), 000000
(V2A)
60 kN
600 bar



EAN 80000
4251269316
135
1
007400 00 0000, 00(St), 000000
(V2A)
60 kN
600 bar



EAN 80005
4251269316
142
1
007400 00 0000, 00(St)
60 kN
600 bar



EAN

80006
4251269316
159
1
00000, 00(St)
60 kN
600 bar

007400 00



EAN

80072
1
000000 (V2A)
60 kN
600 bar

007400 00